

Vaccine Alarm Thermometer



Specifications

Alarm Type: Audible/Visual Alarm

Ambient Operating RH Conditions : 0 to 95% RH (non-condensing)

Ambient Operating Temperature Conditions: 32 to 122F (0 to 50C)

Approvals: CE, ROHS

Battery Life (Avg): 1-Year (at 5-minute sample rate and no alarm conditions) - At Ambient Conditions

Digital Display: Yes

Dimensions: 4.6 x 2.75 x 0.8cm

Display Dimensions Height: 1"

Display Dimensions Width: 1.9"

Display Resolution: 0.1^oF (0.1^oC)

Included Accessories: 2 AA Batteries and Manual, Velcro for mounting, Certificate of Calibration; MM120: 1 Probe in Glycol Bottle

Mounting Options: Wall mount with keyhole or Velcro

Remote Sensor Length: 10 ft.

Response Time: 30 seconds to 63% FS

Sample Interval: Standard = 5 Min; Fast = 1 Min

Sample Storage Rate: Recording Times: Continuous - Updates Min / Max stores only most current reading

Temperature Accuracy: +/-1.8F from 0 to 122F (+/-1C from -18 to 50C)

Temperature Range: -50 to 122F (-50 to 50C)

Temperature Sensor: Thermistor hard wired to PBC, submersible tip sealed in leak-proof glycol bottle

Unit Weight: 3.2 oz (unit only); 4.0 oz (unit, probe, and glycol bottle)

Calibrations

N100 1-Point NIST Traceable Calibration

N300 3-Point NIST Traceable Calibration

Accessories



N520 - Certificate of Validation

Certificate of Validation